

Program LEQ Professional v. 6-2016 dla Windows

Dane do obliczeń - pora dnia:

Źródła punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
1	829.1	768.2	8.0	62.0	
2	838.5	767.0	8.0	62.0	
3	849.0	767.0	8.0	62.0	
4	859.5	767.0	8.0	62.0	
5	870.0	767.0	8.0	62.0	
6	1071.1	718.9	0.8	87.9	
7	1054.0	719.0	0.8	87.9	
8	1039.0	711.0	0.8	87.9	
9	1019.0	701.0	0.8	87.9	
10	1006.0	703.0	0.8	87.7	
11	988.0	703.0	0.8	87.7	
12	989.0	686.0	0.8	87.0	
13	987.5	663.5	0.8	87.0	
14	986.0	641.0	0.8	87.0	
15	970.0	641.0	0.8	87.3	
16	944.0	648.0	0.8	87.3	
17	918.0	655.0	0.8	87.3	
18	971.0	707.0	0.8	87.5	
19	949.0	709.0	0.8	87.5	
20	927.0	711.0	0.8	87.5	
21	910.0	712.0	0.8	87.7	
22	903.0	734.0	0.8	87.7	
23	907.0	749.0	0.8	87.7	
24	909.0	769.0	0.8	87.7	
25	894.0	748.0	0.8	87.1	
26	887.0	724.0	0.8	87.1	
27	870.0	725.0	0.6	78.4	
28	851.0	729.0	0.6	78.4	
29	899.0	714.0	0.6	78.6	
30	922.0	712.0	0.6	78.6	
31	932.0	703.0	0.6	78.6	
32	968.0	709.0	0.6	78.6	
33	989.0	708.0	0.6	78.2	
34	1019.0	710.0	0.6	78.2	
35	1048.0	716.0	0.6	78.2	
36	1065.0	719.0	0.6	78.2	
37	859.0	746.0	0.6	77.8	
38	874.0	742.0	0.6	77.8	
39	878.0	709.0	0.6	77.8	
40	886.0	688.0	0.6	77.8	
41	897.0	672.0	0.6	77.5	
42	907.0	662.0	0.6	77.5	
43	989.0	676.0	0.6	77.5	
44	989.0	651.0	0.6	77.5	
45	993.0	698.0	0.6	77.3	
46	815.0	746.0	0.5	67.7	
47	833.5	745.0	0.5	67.7	

48	852.0	744.0	0.5	67.7
49	885.0	743.0	0.5	66.7
50	884.5	757.0	0.5	66.7
51	884.0	771.0	0.5	66.7
52	843.0	718.0	0.5	66.9
53	844.5	729.5	0.5	66.9
54	846.0	741.0	0.5	66.9
55	865.0	739.0	0.5	66.8
56	878.0	735.0	0.5	66.8
57	863.0	719.0	0.5	66.7
58	879.0	718.0	0.5	66.7
59	828.0	751.0	0.5	78.2
60	814.0	740.0	0.5	78.2
61	848.0	749.0	0.5	78.2
62	863.0	735.0	0.5	78.2
63	879.0	748.0	0.5	77.2
64	895.0	754.0	0.5	77.2
65	911.0	760.0	0.5	77.2
66	903.0	744.0	0.5	77.2
67	901.0	732.5	0.5	77.2
68	899.0	721.0	0.5	77.2
69	922.0	711.0	0.5	78.4
70	944.0	711.0	0.5	78.4
71	982.0	707.0	0.5	78.1
72	1006.0	708.0	0.5	78.1
73	1003.0	708.0	0.5	78.1
74	1032.0	711.0	0.5	78.1
75	1061.0	717.0	0.5	78.2
76	1082.0	719.0	0.5	78.2
77	842.0	740.0	0.5	78.2
78	840.0	725.0	0.5	78.2

=====

Źródła typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	830.9	702.2	830.9	696.5	843.4	691.2	845.3	695.5	0.0	2.2
2	832.8	706.1	846.7	701.3	848.6	704.6	834.2	709.4	0.0	2.2
3	847.7	697.9	853.0	695.0	855.4	698.9	850.1	701.8	0.0	1.0

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr źródła	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
1	sc.1	L wew	115.0							
		R sc	30.0							
	sc.2	L wew	115.0							
		R sc	30.0							
	sc.3	L wew	115.0							
		R sc	30.0							
	sc.4	L wew	115.0							
		R sc	30.0							
	dach	L wew	115.0							
		R d	30.0							

Nr źródła	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
2	sc.1	L wew	115.0							
		R sc	30.0							
	sc.2	L wew	115.0							
		R sc	30.0							
	sc.3	L wew	115.0							
		R sc	30.0							
	sc.4	L wew	115.0							
		R sc	30.0							
	dach	L wew	115.0							
		R d	30.0							

Nr źródła	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
3	sc.1	L wew	88.0							
		R sc	0.0							
	sc.2	L wew	88.0							
		R sc	0.0							
	sc.3	L wew	88.0							
		R sc	0.0							
	sc.4	L wew	88.0							
		R sc	0.0							
	dach	L wew	88.0							
		R d	0.0							

Ekran akustyczny :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	821.8	736.8	820.3	716.2	831.4	715.7	832.3	736.8	0.0	3.5
2	912.0	717.6	1006.1	712.8	1008.5	769.0	915.4	773.3	0.0	4.0

WSPÓŁCZYNNIKI ODBICIA DLA ŚCIAN

Nr	ściana 1	ściana 2	ściana 3	ściana 4	dach
1	1.0000	1.0000	1.0000	1.0000	1.0000
2	1.0000	1.0000	1.0000	0.3000	0.3000