

Program LEQ Professional v. 6-2019 dla Windows

\*\*\*\*\*

Dane do obliczeń - pora dnia:

\*\*\*\*\*

Źródła punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
1	829.0	766.2	8.0	58.0	
2	838.9	765.7	8.0	58.0	
3	848.8	765.2	8.0	58.0	
4	858.7	764.7	8.0	58.0	
5	868.6	764.2	8.0	58.0	
6	836.4	696.8	2.2	68.0	
7	840.9	704.8	2.2	68.0	
8	906.4	703.1	0.2	74.0	
9	908.5	707.2	0.2	74.0	
10	892.8	706.5	0.2	74.0	
11	918.3	683.4	0.2	74.0	
12	916.8	666.5	0.2	74.0	
13	934.5	665.0	0.2	74.0	
14	937.0	681.6	0.2	74.0	
15	951.0	670.4	0.2	74.0	
16	950.0	651.4	0.2	74.0	
17	967.6	650.6	0.2	74.0	
18	969.8	669.0	0.2	74.0	
19	943.8	701.0	0.2	74.0	
20	955.4	680.9	0.2	74.0	
21	966.2	702.5	0.2	74.0	
22	862.2	701.3	0.8	87.1	
23	878.3	678.4	0.8	87.1	
24	901.7	658.6	0.8	87.1	
25	944.3	645.1	0.8	87.1	
26	994.1	634.6	0.8	87.1	
27	990.1	683.1	0.8	87.1	
28	963.6	709.6	0.8	88.9	
29	915.7	704.9	0.8	88.9	
30	887.1	720.5	0.8	88.9	
31	897.0	746.0	0.8	88.9	
32	1015.6	708.6	0.8	88.9	
33	1046.2	713.8	0.8	88.9	
34	876.7	726.8	0.8	88.9	
35	859.0	725.2	0.8	88.9	
36	909.0	771.5	0.8	88.9	
37	913.6	763.0	0.8	87.1	
38	910.0	724.7	0.8	87.1	
39	873.1	743.9	0.8	87.1	
40	886.6	768.4	0.0	87.1	
41	846.0	742.9	0.0	87.1	
42	849.1	733.0	0.8	87.1	
43	995.3	707.0	0.8	81.0	
44	1014.0	695.0	0.8	81.0	
45	1041.0	720.5	0.8	81.0	
46	1081.1	720.5	0.8	81.0	
47	1067.6	745.5	0.8	81.0	

48	1066.0	691.4	0.8	81.4
49	1041.0	697.6	0.8	81.4
50	1010.4	676.3	0.8	81.4
51	966.2	639.9	0.8	81.4
52	924.0	654.5	0.8	81.4
53	900.1	683.6	0.8	81.4
54	822.1	743.9	0.8	81.4
55	1052.2	710.1	0.8	81.4
56	974.0	708.0	0.8	81.0
57	883.0	746.5	0.8	81.0
58	858.0	719.5	0.8	81.0
59	883.0	694.0	0.8	81.0
60	884.0	719.5	0.8	81.0
61	934.4	710.1	0.8	81.0
62	983.5	633.6	0.8	79.5
63	946.1	710.4	0.8	79.5
64	1035.3	712.7	0.8	79.5
65	1066.5	732.0	0.8	79.5
66	1075.9	715.8	0.8	79.5
67	1065.0	707.5	0.8	80.5
68	1000.8	696.5	0.8	80.5
69	998.4	652.8	0.8	80.5
70	936.0	648.0	0.8	80.5
71	864.2	742.9	0.8	80.5
72	899.1	672.2	0.8	80.5
73	914.2	655.5	0.8	80.5
74	870.5	691.4	0.8	79.5
75	875.2	717.9	0.8	79.5
76	912.1	744.4	0.8	79.5
77	935.5	699.2	0.8	79.5
78	954.2	643.2	0.5	70.3
79	894.7	702.2	0.5	70.3
80	864.2	736.1	0.5	70.3
81	887.1	706.0	0.5	70.3
82	893.4	672.2	0.5	68.5
83	1026.7	685.4	0.5	68.5
84	843.4	718.1	0.5	68.5
85	837.7	740.3	0.5	68.5
86	1022.9	701.8	0.5	68.5
87	983.5	633.6	0.5	68.5

=====

Źródła typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	840.2	705.8	844.5	704.4	843.7	702.5	839.3	704.0	0.0	2.2
2	836.0	697.8	840.3	696.4	839.5	694.5	835.1	696.0	0.0	2.2
3	851.2	698.3	851.6	698.8	852.9	698.0	852.5	697.3	0.0	1.0
4	850.5	697.3	851.0	697.9	852.2	696.9	851.7	696.3	0.0	1.0
5	875.9	759.4	886.4	759.4	886.4	756.2	875.9	756.2	0.0	18.3

=====

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr źródła	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.

```

1  sc.1  L wew  110.6
      R sc   25.0
   sc.2  L wew  110.6
      R sc   25.0
   sc.3  L wew  110.6
      R sc   25.0
   sc.4  L wew  110.6
      R sc   25.0
   dach  L wew  110.6
      R d    25.0

```

```

=====
Nr źródła      A   63   125   250   500  1000  2000  4000  8000  wsp.odp.
=====

```

```

2  sc.1  L wew  110.6
      R sc   25.0
   sc.2  L wew  110.6
      R sc   25.0
   sc.3  L wew  110.6
      R sc   25.0
   sc.4  L wew  110.6
      R sc   25.0
   dach  L wew  110.6
      R d    25.0

```

```

=====
Nr źródła      A   63   125   250   500  1000  2000  4000  8000  wsp.odp.
=====

```

```

3  sc.1  L wew   84.0
      R sc   20.0
   sc.2  L wew   84.0
      R sc   20.0
   sc.3  L wew   84.0
      R sc   20.0
   sc.4  L wew   84.0
      R sc   20.0
   dach  L wew   84.0
      R d    20.0

```

```

=====
Nr źródła      A   63   125   250   500  1000  2000  4000  8000  wsp.odp.
=====

```

```

4  sc.1  L wew   84.0
      R sc   20.0
   sc.2  L wew   84.0
      R sc   20.0
   sc.3  L wew   84.0
      R sc   20.0
   sc.4  L wew   84.0
      R sc   20.0
   dach  L wew   84.0
      R d    20.0

```

```

=====
Nr źródła      A   63   125   250   500  1000  2000  4000  8000  wsp.odp.
=====

```

```

5  sc.1  L wew   99.8
      R sc   20.0
   sc.2  L wew   99.8
      R sc   20.0

```

```

sc.3 L wew 99.8
      R sc  20.0
sc.4 L wew 99.8
      R sc  20.0
dach L wew 99.8
      R d   20.0

```

=====

Ekranry akustyczne :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	821.8	736.8	821.8	716.2	832.3	716.2	832.3	736.8	0.0	3.5
2	912.0	717.6	1006.1	712.8	1008.5	769.0	915.4	773.3	0.0	4.0
3	823.4	777.6	875.3	775.7	874.0	753.3	822.2	755.8	0.0	8.0

WSPÓŁCZYNNIKI ODBICIA DLA ŚCIAN

Nr	ściana 1	ściana 2	ściana 3	ściana 4	dach
1	1.0000	1.0000	0.8000	1.0000	1.0000
2	1.0000	1.0000	1.0000	0.3000	0.3000
3	1.0000	1.0000	0.8000	1.0000	1.0000